

EXPRESS MAIL LABEL NO. EM424872241US Date of Deposit: November 30, 1998

WYC/DJC:am 11/30/98 MS126644

PATENT Attorney's Ref. No. 3382-51386



# IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

Box PATENT APPLICATION
TO THE ASSISTANT COMMISSIONER FOR PATENTS
Washington, D.C. 20231

Transmitted herewith for filing is the patent application of:

Inventor(s): J. Wiltse Carpenter, Timo Bruck, and Lee S. Mighdoll

For: PROXY FOR VIDEO ON DEMAND SERVER CONTROL

Enclosed are:

13 pages of specification, 5 pages of claims, an abstract and a Combined Declaration and Power of Attorney.

Please return the enclosed postcard to confirm that the items listed above have been received.

Respectfully submitted,

KLARQUIST SPARKMAN CAMPBELL LEIGH & WHINSTON, LLP

Donna Jo Coningsby Registration No. 41,684

One World Trade Center, Suite 1600 121 S.W. Salmon Street Portland, Oregon 97204

Telephone: (503) 226-7391 Facsimile: (503) 228-9446

cc: MS Docketing (MS Ref. No. 126644)

William Y. Conwell, Esq. Docketing Secretary Megan Thomas

12

1.2 miles 15 th

**15** 

så

#### PROXY FOR VIDEO ON DEMAND SERVER CONTROL

#### Related Application Data

The subject matter of this application is generally related to that disclosed in 5 the following applications filed contemporaneously herewith:

Video on Demand Methods and Systems (White et al);

Method and System for Presenting Television Programming and Interactive Entertainment (White et al); and

Interactive Video Programming Methods (White et al).

The subject matter of this application is also generally related to the subject matter of application 09/153,577, filed September 15, 1998.

The disclosures of these related applications are incorporated by reference.

### Field of the Invention

The present invention relates generally to interactive entertainment systems, and more particularly relates to the use of a processor between the head-end and the clients, to which various processing tasks can advantageously be delegated.

## Background and Summary of the Invention

The popularity of the Internet, a well-known, global network of cooperative interconnected computer networks, combined with the widespread availability of low-cost broadband networking and advanced digital compression techniques, has spurred the growth of what is known as interactive television. Interactive television provides viewers with compelling Internet and video content on their home television equipped only with a simple internet-television terminal, such as those pioneered by WebTV Networks, Inc. WebTV terminals are akin to the settop boxes associated with a cable television network, and work in conjunction with a standard home television set to display both Internet and traditional television

**PATENT** 

content, so that persons without access to a personal computer are able to access the Internet.

The ability to combine video content with the interactive features of interactive television has spawned numerous providers of video-on-demand

5 applications for interactive entertainment systems. Currently, the typical video-on-demand application for interactive television consists of plural video-on-demand clients on terminals attached to the viewer's home television, and one or more video-on-demand servers connected to the video head-end. The user interface of current video-on-demand applications is contained entirely in the video-on-demand client, and provides commands to the video-on-demand server to select, start or stop and pay for the video played on the viewer's home television. Typically, the video-on-demand server provides access to the video content available for transmission, whereas the client controls the selection of the video and the payment mechanism.

There are several different brands of video-on-demand applications available on the market today. Three examples are Seachange, Vivid and Microsoft's Netshow Theater. In view of the popularity of the video-on-demand feature of interactive television, there will likely be many more video-on-demand servers developed in the near future.

One of the difficulties with the proliferation of competing video-on-demand applications is the lack of an industry standard communications protocol. The protocol controls the communication between the video-on-demand server and the various video-on-demand clients on the interactive television network. The challenge in a video-on-demand application is that it must be capable of managing not only the download of digital video data to the client, but also the transmission of control data to and from the client relating to system administration (e.g. channel assignment data, billing information, etc.).

T.

He half than

Section of the sectio

ڐم ςĒ

ıД

Currently, most video-on-demand servers use a proprietary communications protocol unique to that video-on-demand server. Problems arise when the protocols used to control the video-on-demand servers aren't understood (are incompatible with) the protocols supported by the various video-on-demand clients.

5 Examples of some of the diverse protocols in use today are DAVEC (a cable modem standard), DSMTC (used by certain video head-ends), and RTSP (an industry-proposed standard that has met with little success). The use of incompatible protocols has limited expansion options available to existing video on demand systems.

Moreover, the current configuration of most interactive video systems provide incomplete failover recoverability since the back-end servers on which most video-on-demand servers reside necessarily cannot completely manage their own failure.

Current video-on-demand servers use a limiting "segmented channel" model 15 to transmit the video data. Under this model, each viewer is assigned a dedicated video channel. This greatly limits flexibility and expansion options.

Various embodiments of the present invention redress these and other shortcomings of the prior art by interposing a middle tier in the interactive video system. This middle tier -- commonly a proxy server -- provides various services, 20 including protocol translation, system administration (dynamic channel assignment, load distribution, and failover), dynamic error-patching, and security.

According to one aspect, the invention provides an improved system and method for delivering a video-on-demand feature to remote clients of an interactive television network. The system and method employ the proxy server to 25 reconfigure the components of a video-on-demand application into a flexible multitiered configuration, and to redistribute the functions of those components to the proxy server so as to enhance the performance, reliability, security, scalability and other features of the system.

One implementation of the present invention includes one or more proxy servers interposed between one or more video-on-demand servers and one or more video-on-demand clients. The proxy server includes a protocol translation component, a user interface component, a channel management component, a 5 loadsharing component, a failover component and a security component.

The translation component translates, if necessary, the communication protocols used by the video-on-demand server and video-on-demand client, and fixes -- on-the-fly -- certain errors in those protocols. The user interface component distributes the user interface between the video-on-demand server and 10 video-on-demand client and provides user interface enhancements. The channel management component manages the assignment of transmission channels to video-on-demand clients. The failover component redirects requests to failed video-on-demand servers to secondary/alternate servers. The loadsharing component manages the load between the video-on-demand servers and possibly 5 one or more other proxy servers in a given server configuration of the interactive television network at the head-end. The security component provides a uniform security framework that previously was located in each individual video-on-demand server at the head-end.

In one implementation of the method and system, a promotional component 20 is also provided to initiate delivery of customized promotional content from the proxy server to the video-on-demand client.

The foregoing and other features and advantages of the present invention will be more readily apparent from the following detailed description, which proceeds with reference to the accompanying drawings.

25

ij

III. III.

gă. i a in

# Brief Description of the Drawings

Figure 1 is a block diagram of an interactive video system that can be used in accordance with the present invention.

**PATENT** 

The first

5

Figure 2 is a block diagram of the entertainment video head-end of Figure 1.

Figure 3 is a block diagram of video-on-demand components.

Figure 4 is a block diagram of a configuration of a video-on-demand application.

Figure 5 is a block diagram of a proxy server of Figure 1.

#### **Detailed Description**

Referring to Figure 1, an exemplary interactive entertainment system 10 according to one embodiment of the present invention includes an entertainment 10 head-end 12, one or more proxy servers 24, and one or more client terminals 14 intercoupled through a network 16. The proxy servers 24 are computers interposed in a middle tier between the head-end 12 and the client terminals 14 to perform various interactive video system control and user interface (UI) functions.

The network 16 typically comprises coaxial cable or optical fiber 18,

extending from the head-end 12 to distribution nodes 20 within various

neighborhoods. From the distribution nodes, further cables 22 couple to individual subscriber premises.

The proxy server 24 is interposed in a logical TCP/IP control channel 27 between the head-end and clients. While the control signals and the entertainment 20 are physically conveyed on the same cable 18, they are shown separately in Fig. 1 for conceptual clarity.

As shown in Figure 2, the entertainment head-end 12 includes the components typically associated with a cable television head-end installation, e.g. satellite receivers 26 for receiving satellite broadcasts and producing corresponding baseband analog video signals. Additionally, head-end 12 includes fast digital disk arrays and/or optical storage 28 for storage of MPEG-encoded digital video for ondemand delivery. Head-end 12 also includes one or more interactive services servers 30, which output HTML-based programming (e.g. customized news,

H R RING

jaš.

fei

1

1

celebrity chat, interactive jukebox, and interactive games), as further detailed in the related applications by White et al.

The illustrated head-end 12 is shown as including the proxy servers 24. In some implementations, such servers are co-located at the head-end; in others, the 5 proxy servers are remote from the head-end.

The transmission of the various forms of data from head-end 12 over the network 16 is straightforward. As is familiar to those skilled in the video arts, the analog video is commonly distributed on 6 MHz channels, beginning at 52 MHz and extending upwardly. The digital video can be encoded on a carrier for 10 transmission within one of these conventional broadcast channels, or can be modulated at one or more other unused frequencies. Statistical multiplexing is desirably employed to transmit plural channels of digitized video with reduced bandwidth. The HTML-based interactive services and the control data can be transmitted using a conventional protocol (e.g. TCP/IP) and modulated onto a 15 suitable carrier frequency for distribution over the network. After modulation to appropriate distribution frequencies by modulators 34, these various signals are combined by an RF combiner 36 for distribution over the network 16.

Referring to the top portion of Figure 3, a typical prior art video-on-demand system includes a client terminal 14 intercoupled to a video-on-demand server 30 20 in head-end 12 through a network 16. The client terminal 14 includes a client user interface (UI) 56 to perform various interactive video system control functions, such as video selection, start, stop and payment. The video-on-demand back-end server 30 is a computer, usually co-located with the interactive services server 30, and may include a failover component 70, a loadsharing component 74 and a 25 security component 76 to perform various interactive video system control functions such as receiving and transmitting control data relating to system administration (e.g. channel assignment data, billing information, etc.), error recovery and load management.

1D

The state of

15

a ä

is is

T.

Referring to the bottom portion of Figure 3, the illustrated implementation of the present invention interposes a proxy server 24 between the client terminal 14 and the video-on-demand server 30. In the new configuration the UI function is now shared between the client UI 56 on the client terminal 14 and the server UI 578 on the proxy server 24. The video-on-demand back-end server 30 no longer contains the failover component 70, loadsharing component 74 or security component 76. Those functions have been distributed instead to the proxy server 24.

The top portion of Fig. 4 shows another representation of a prior art video10 on-demand system, and the lower portion shows an embodiment of the present invention. As is familiar to those skilled in the relevant arts, a security firewall 80 is commonly provided to limit access to the video-on-demand back-end servers 30 (the bi-directional control data 82 is typically transmitted over an unsecured IP link).

Focusing on the bottom portion of Figure 4, the illustrated embodiment interposes the proxy server 24 between the client 14 and the video-on-demand back-end server 30. The introduction of the proxy server 24 greatly enhances the configurability of the interactive video system. The back-end servers still transmit the MPEG encoded video data 84 directly to the RF combiners 36. But by 20 separately managing the control data 82 flowing between the clients 14 and multiple back end servers 30, the proxy server 24 serves as an additional security layer -- insulating the back end video-on-demand servers 30 from the IP link over which the control data 82 is transmitted. Configured in this way, the back-end video-on-demand servers 30 may be used more as a commodity available to one or 25 more proxy servers 24 in the transmission of MPEG encoded video data 84 from the back-end server 30 to the client terminal 14.

**PATENT** 

Moreover, the proxy server 24 can perform various administrative management functions, such as managing channel assignments for video-ondemand transmission.

Here a distinction should be drawn between two types of "channels." The 5 first, termed a "transmission channel," refers to an actual frequency channel (e.g. 52 - 58 MHz) that is used to relay programming from the head-end 12 to the client terminal 14 over the network 16. The second, termed a "viewer channel," refers to the moniker (e.g. MSNBC, CNN, GAME, CHAT, VIDEO) by which a user distinguishes different programming. The mapping between viewer and 10 transmission channels is determined by the system, e.g. proxy server 24.

The VIDEO channel is a viewer channel -- it is the channel to which the viewer switches to receive video-on-demand programming. The frequency over which this programming is delivered is not important to the viewer. Different transmission channels may be available for use at different times, depending 15 system resource usage (e.g. other viewers' video-on-demand usage). One day the 108-114 MHz transmission channel might be used to relay on-demand video to a subscriber. The next day, the 114-120 MHz transmission channel might be used instead. Data indicating the assignment of transmission channels-to-viewer channels is periodically sent as control data 82 between the proxy server 24 and 20 the client terminal 14.

If a viewer interrupts delivery of an on-demand video, e.g. by switching to another channel or pressing STOP on a control panel (as further detailed in the related application by White et al), transmission of the video is suspended. The proxy maintains the assignment of the original transmission channel to that client 25 briefly, but if the video is not promptly resumed, that transmission channel is returned by the proxy server 24 to a pool of available transmission channels. If the viewer thereafter returns to the VIDEO channel (or presses PLAY on a control panel), this fact is communicated to the proxy server 24 by the client terminal over

the control data link. The proxy server 24 then identifies an available transmission channel and instructs the client terminal 14 to tune to that channel. (This retuning is transparent to the viewer, whose channel selection remains at the VIDEO viewer channel.) The proxy server 24 similarly instructs the video server 30 to resume 5 transmission of the requested video from the point of interruption, or just before the point of interruption (for purposes of viewing context), this time modulating it on the newly-assigned channel. Video delivery resumes. However, unknown to the viewer, the video delivery resumes on a transmission frequency different than that originally used.

In addition to managing system resources such as transmission channels, the proxy server 24 also serves as a convenient control point for administering certain UI functions on the client terminals 14. Thus, for example, a videoselection UI by which a viewer selects a desired video from a library of available videos can be defined at the proxy server 24 (which is in constant communication 15 with the back end server's video library data), and distributed to the clients 14 as needed. (These UI elements at the proxy server include HTML instructions that are sent to the client for rendering to produce the desired user interface screens and controls.)

Similarly, by controlling from the proxy server certain client UI elements (e.g. 20 buttons, controls, graphics, labels, and other screen customizations presented to the viewer on the client terminal), it is possible to update the UI elements with new features, or to apply changes to reflect new promotional features or different branding, as needed. For example, the logo of a particular video-on-demand server may appear on a button on a UI screen presented to a viewer. The server UI 78 of 25 the proxy server 24 can dynamically change that logo as it appears on the various client terminals 14 to reflect the branding of the various video-on-demand back-end servers 30 it controls.

**PATENT** 

5

In contrast, primitives defining other UIs are maintained at the client terminal 14. An example is a video playback UI, with PLAY, STOP, REWIND, etc., buttons. This UI is well defined and static, so there is less advantage to distributing its definition out to the proxy server.

A viewer operating the client terminal 14 is unaware of the origin of the UIs presented on the viewing screen. The viewer may invoke a video playback UI (originating at the client terminal) to stop playback of an on-demand video. After pressing STOP, the system may immediately present a further UI (originating at the proxy server) indicating that the viewer has electronic mail waiting, or indicating 10 the time-remaining in the interrupted video.

Another function of the illustrated proxy server 24 is to effect protocol translation between the protocol employed by the client, and that employed by the server. As noted, there are a wide variety of such protocols. While new video-ondemand systems are commonly installed with a consistent client/server protocol, subsequent events can lead to changes. For example, by acquisition or otherwise, an operator of a video-on-demand system may inherit client terminals from another (non-compatible) system. The provision of protocol translation in the proxy server facilitates integration of such non-compatible client terminals into the system. Similarly, upgrades to a video-on-demand system may entail substitution of a video 20 server employing a different control protocol. Again, protocol translation by the proxy server facilitates integration of such new equipment.

Still another function of illustrated proxy server 24 is loadsharing and failover administration. In the loadsharing component 74, the proxy server 24 monitors the loads on the various video-on-demand back-end servers 30 under its 25 control, and allocates the video-on-demand viewing load accordingly. (In an exemplary embodiment, the head-end includes several video servers. Currently popular movie titles may be replicated in several of the servers to accommodate

1,1

==

sä

i să

12.

their expected high demand. Older, classic films, in contrast, may be present on just one server.)

Loadsharing 74 works in conjunction with the failover 70 function, where the proxy server 24 redirects requests to failed back-end servers 30 to other 5 available servers. In this way, the proxy server 24 enhances performance by managing what would likely be a catastrophic failure in the prior art configuration of video entertainment systems 10.

Yet another function of the illustrated proxy server 24 is to fix -- on-the-fly -certain problems associated with either a client or a server. For example, a certain 10 client may, in a particular circumstance, erroneously send two PLAY commands when only one should be sent. The proxy server can be programmed to look for such aberrant behavior, and pass on to the video server only a single PLAY command. Similarly, a video server may have a bug in a JPEG compression routine that causes certain image data transmitted from the server to be flawed, prompting 15 a receiving client to fail. The proxy server can monitor the traffic from the server for such corrupted JPEG data, and can correct it before passing same to the client. (It will be recognized that this general capability is widely applicable, and is not limited to the particular bug-fixes given in these examples.)

Fig. 5 is a block diagram of an exemplary proxy server 24. The illustrated 20 server includes a CPU 38, RAM memory 40, non-volatile memory 42, a user interface (UI) 78, and appropriate interfaces to the RF combiners 36 and back-end video-on-demand servers 30.

The CPU 38 can be any of several microprocessors, e.g. those available from Intel, AMD, Cyrix, Motorola, etc. Alternatively, the CPU 38 can be a custom 25 device that optionally integrates one or more of the other components of proxy server 24.

The RAM memory 40 typically comprises 256K of EDO memory, but more or less memory, and/or memory of differing type, can alternatively be used.

1,1

North William II

15

a di

2.2

ij

The non-volatile memory 42 in the illustrated embodiment includes a ROM,

EEPROM, or flash memory in which certain components of the server's operating system and applications software are stored. Additionally, the illustrated non-volatile memory 42 includes 4GB of magnetic disk storage. Software stored in this non-volatile memory (commonly transferred to the RAM memory for execution) causes the proxy server 24 to perform the various functions detailed earlier. (Such programming is well within the capabilities of artisans in this field, so is not belabored.)

Having described and illustrated the principles of our invention with

10 reference to a preferred embodiment and various alternatives, it should be apparent
that the invention is not limited to the detailed arrangements.

For example, while the detailed proxy server 24 performed a certain set of functions, in other embodiments such a server can perform a subset (or superset) of these functions.

While the disclosure particularly detailed the proxy server's 24 role in defining aspects of a visual UI presented on the client terminal 14, in other embodiments, the proxy can play a similar role with UIs of other types (e.g. gesture-interfaces, audio interfaces, tactile interfaces, etc.).

Reference was made to HTML. This term is meant to include not just

20 Hypertext Markup Language per se, but also to encompass other graphical and/or video representation systems by which primitives can be combined to yield desired static or moving displays.

The illustrated embodiment employed a wired link to the interactive network, but other distribution arrangements (e.g. direct satellite broadcast, with telephone 25 return channel) can likewise by used. Similarly, the dial-up link is not exclusive; other arrangements (e.g. MetroCOM, etc.) can be used, depending on the needs of the particular application.

1

ıD

1 Hard of the

ı ä

Moreover, even a "wired" link to the interactive network needn't be of the sort particularly illustrated. With enhanced compression techniques and delivery technologies, other arrangements -- including plain old telephone service -- can alternatively be employed.

To provide a comprehensive disclosure without unduly lengthening this specification, applicants incorporate by reference the disclosure of patent 5,648,824, which discloses additional details related to video-on-demand systems and related user interfaces.

While the foregoing discussion has detailed a complete system, it employs 10 many inventive concepts - each of which is believed patentable apart from the system as a whole.

In view of the many different embodiments to which the above-described inventive concepts may be applied, it should be recognized that the detailed embodiments are illustrative only and should not be taken as limiting the scope of 15 our invention. Rather, we claim as our invention all such modifications as come within the scope and spirit of the following claims, and equivalents thereto.

#### WE CLAIM:

The state of the s

r i

ij

20

25

- A video system comprising a video-on-demand server and a remote client, the server employing a server communications protocol, the client
   employing a client communications protocol, the system further including a proxy interposed between the server and the client, the proxy including means for translating between the server and client communications protocols, wherein the server and client can communicate through the proxy even if the server and client protocols are different, and wherein change to either the server or client protocol
   can be accommodated by a change to the proxy rather than to the client or server, respectively.
  - 2. The system of claim 1 wherein the proxy further includes means for translating between at least one of said client and server communications protocols and a third protocol different from said client and server communications protocols, wherein the same proxy can be used in different server/client environments.
  - 3. The system of claim 1 wherein the proxy includes means for ameliorating aberrant behavior in at least one of said server or client.
  - 4. The system of claim 3 wherein the proxy includes means for detecting a predetermined input communication in an input protocol, and issuing an output communication in an output protocol that does not exactly correspond to the input communication.
  - 5. In a video-on-demand application including plural user terminals and an infrastructure linking the terminals to one or more video servers, a method comprising:

1

all all

ıij

presenting a user interface on a screen associated with one of said terminals, the user interface comprising plural elements;

specifying a first group of user interface elements in accordance with first instructions stored in the user terminal; and

specifying a second group of user interface elements in accordance with second instructions received by the user terminal from the infrastructure.

- 6. The method of claim 5 further comprising providing a proxy as part of the infrastructure, and issuing said second instructions from the proxy.
- 7. The method of claim 5 wherein the first and second user interface elements are presented at different times.
- 8. The method of claim 5 wherein the first group of user interface elements include controls for video-on-demand playback, and the second group of user interface elements include controls for video-on-demand selection.
  - 9. The method of claim 5 wherein the second instructions include graphic data, the method including using said graphic data for logo branding of the user 20 interface.
  - 10. The method of claim 5 comprising interrupting delivery of an on-demand video in response to a user command input through one of said first group of user interface elements, and presenting a screen display including at least one of said
    25 second group of user interface elements in response.
    - 11. The method of claim 10 wherein said screen display indicates whether the viewer has electronic mail waiting.

- 12. The method of claim 10 wherein said screen display indicates time remaining for the interrupted on-demand video.
- 5 In a video-on-demand application having a client coupled to a server, the system including a user interface component, an improvement comprising interposing between the client and the server an intermediary processor, and distributing at least part of the user interface component between the client and the intermediary processor.

13 123

ı,Z

14. The system of claim 13 further including a security component, the method including distributing at least part of the security component to the intermediary processor.

15

15. The system of claim 13 further including a failover component, the method including distributing at least part of the failover component to the intermediary processor.

- 16. The system of claim 13 wherein the intermediary serves as a protocol 20 converter between the client and server.
- 17. In a video-on-demand application including plural clients coupled to at least one video server through an infrastructure, the infrastructure defining plural transmission channels, the infrastructure further including an intermediary 25 processor, a method comprising:

assigning a first transmission channel to a first client to transmit an ondemand video thereto;

assigning a second transmission channel to a second client to transmit an on-demand video thereto; and

employing the intermediary processor to manage said assignment of channels to clients.

5

18. The method of claim 17, including employing the intermediary processor to reassign the first client to a third transmission channel at a point between the beginning and end of the first client's on-demand video, so as to manage channel resources.

10

111

17.

19. The method of claim 17 wherein the clients and server employ different communication protocols, and the intermediary processor effects conversion between said protocols.

**-**15

20. In a video-on-demand application including plural clients coupled to a primary video server through an infrastructure, the infrastructure including a proxy, the system further comprising at least one backup video server, a method comprising:

20

123

using said proxy as a firewall between the clients and the video servers; and also using said proxy to manage redirection of video sourcing from the primary video server to the backup video server in the event of failure of the primary video server.

21. The method of claim 20, further comprising using the proxy to specify 25 at least a portion of a user interface presented on a client display.

13

ıD

N

[all

22. In a video-on-demand application including plural clients coupled to a video server through an infrastructure, the infrastructure including a proxy, the video server including plural video storage systems, a method comprising:

using said proxy as a firewall between the clients and the video servers; and 5 also using said proxy to manage load distribution among said plural video storage systems.

- 23. The method of claim 22, further comprising using the proxy to specify at least a portion of a user interface presented on a client display.
- 24. In a video-on-demand application including plural clients coupled to at least one video server through an infrastructure, an improvement comprising: providing an intermediary processor in the infrastructure; and initiating delivery of promotional video to a client from the intermediary 15 processor.

#### PROXY FOR VIDEO ON DEMAND SERVER CONTROL

## Abstract of the Disclosure

A video on demand system includes a head-end coupled through a proxy 5 server to plural client terminals. The proxy server performs (or cooperates with another component in performing) various functions, including user interface definition, security, system administration (e.g. channel management, load distribution, and failover), and protocol translation.

1. The control of the




Fig. 1




Fig. 5




Fig. 2




Fig. 3




Fig. 4

# COMBINED DECLARATION AND POWER OF ATTORNEY FOR PATENT APPLICATION

As a below named inventor, I hereby declare that:

My residence, post office address and citizenship are as stated below next to my name,

I believe I am the original, first and sole inventor (if only one name is listed below) or an original, first and joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention entitled PROXY FOR VIDEO ON DEMAND SERVER CONTROL, the specification of which

[X]	is attached here	eto.		
[]	was filed on	as Applicat	ion No	
[]			ternational Application, and as amended (if applicable).	
[]	and was amend	led on	(if applicable).	
[]	with amendmer	nts through	(if applicable).	
specifi			nd understand the contents of led by any amendment referr	
the co that di inform	7, Code of Feder nditions specified sclosed in the pr ation as defined	al Regulations, § 1.56 d in 35 U.S.C. § 120 vior copending application 37 CFR § 1.56 whi	nformation which is material 6. If this is a continuation-in- which discloses and claims stion, I further acknowledge the cocurred between the filitional filling date of the continu	-part application filed under ubject matter in addition to he duty to disclose material ng date of the prior
design also id Interna filed b	n application(s) for ating at least one entified below are ational application	or patent or inventor's e country other than t ny foreign application( n(s) designating at lea	es under Title 35, United States certificate or of any PCT Intended Intended States of America (s) for patent or inventor's ceast one country other than thing a filing date before that or	ternational application(s) listed below and have ertificate or any PCT e United States of America
	Prior Foreign Application(s)			Priority Claimed
	(Number)	(Country)	(Day/Month/Year Filed)	[] [] Yes No

I hereby claim the benefit under Title 35, United States Code, § 119(e) of any United States provisional application(s) listed below:

Application Number	Filing Date

I hereby claim the benefit under Title 35, United States Code, § 120 of any United States application(s) or § 365(c) of any PCT International application(s) designating the United States, listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States or PCT International application in the manner provided by the first paragraph of Title 35, United States Code, § 112, I acknowledge the duty to disclose material information as defined in Title 37, Code of Federal Regulations, § 1.56(a) which occurred between the filing date of the prior application and the national or PCT International filing date of this application:

(Application No.)	(Filing Date)	(Status: patented,
		Pending, abandoned)

The undersigned hereby authorizes the U.S. attorney or agent named herein to accept and follow instructions from \_\_\_\_\_ as to any action to be taken in the Patent and Trademark Office regarding this application without direct communication between the U.S. attorney or agent and the undersigned. In the event of a change in the persons from whom instructions may be taken, the U.S. attorney or agent named herein will be so notified by the undersigned.

I hereby appoint the following attorney(s) and/or agent(s) to prosecute this application, to file a corresponding international application, and to transact all business in the Patent and Trademark Office connected therewith:

Name	Reg. No.	Name	Reg. No.
Kenneth S. Klarquist	16,445	Garth A. Winn	33,220
James Campbell	19,978	Stephen A. Wight	37,759
James S. Leigh	20,434	Joel R. Meyer	37,677
Arthur L. Whinston	19,155	Joseph T. Jakubek	34,190
David P. Petersen	28,106	Robert F. Scotti	39,830
Richard J. Polley	28,107	Gregory V. Bean	36,448
Ramon A. Klitzke II	30,188	David J. Earp	41,401
William Y. Conwell	31,943	Lisa M. Caldwell	41,653
Mark L. Becker	31,325	Donna Jo Coningsby	41,684
William D. Noonan	30,878	Michael D. Jones	41,879
John D. Vandenberg	31,312	Steven D. Yates	42,242
John W. Stuart	24,540	Gregory L. Maurer	P43,781
Donald L. Stephens Jr.	34,022	Adam W. Bell	P43,490
Stacey C. Slater	36,011	Paula A. DeGrandis	P43,581
Katie E. Sako	32,628	Daniel D. Crouse	32,022

Address all telephone calls to Donna J. Coningsby at telephone number (503) 226-7391.

Address all correspondence to:

KLARQUIST SPARKMAN CAMPBELL LEIGH & WHINSTON, LLP One World Trade Center, Suite 1600 121 S.W. Salmon Street Portland, OR 97204-2988

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States-Code and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

Full Name of Sole or first Inventor: J. Wiltse Carpenter	
Inventor's Signature	
Residence: 439 Elizabeth Street, San Francisco, California 94114	Date
Citizenship: United States of America	
Post Office Address: Same as above	
Full Name of Second Joint Inventor, if any: Timo Bruck	
Inventor's Signature	
Residence: 1983-9 San Luis, Mountain View, California 94043	Date
Citizenship: United States of America	
Post Office Address: Same as above	
Full Name of Third Joint Inventor, if any: Lee S. Mighdoll	
Inventor's Signature	
Residence: 801-B Wisconsin Street, San Francisco, California 94107	Date
Citizenship: United States of America	
Post Office Address: Same as above	